AMENDMENTS TO THE CLAIMS

1.-6. (Canceled)

7. (Currently Amended) A lip-type seal for sealing an outer periphery of a shaftsupported by a housing, said lip-type seal-scal system comprising:

a shaft supported by a housing;

an elastic seal ring including an annular fitted part and a lip part, said annular fitted part to be fitted into a hole of the housing, said lip part extending from said fitted part inwardly in a radial direction in the shape of a substantially conical ring that is to be brought into contact with an outer periphery of said the shaft; and

a support ring including an annular joint part joined to said annular fitted part, and an annular supporting part, said annular supporting part defining a hole through which the said shaft is to pass, extending from a side of said annular joint part to a middle region of said lip part, and supporting said lip part, from inwardly of said lip part, in the radial direction,

wherein said lip part is formed so as to extend linearly when high pressure is not applied to said lip part and be tapered in cross section from an area at which non-contact with said annular supporting part begins toward an end of said lip part, such that a value of T0/T1 falls within 0.3 to 0.7, with T1 being a thickness of said lip part at the area at which non-contact with said annular supporting part begins, and T0 being a thickness of said end of said lip part, and such that a value (D1-D0/D1 falls within 0.03 to 0.15, with D0 being an inner diameter of said end of said lip part, and D1 being an outer diameter of the said shaft.

8. (Canceled)

(Currently Amended) The lip-type-scal system according to claim 7, wherein
an end of said annular supporting part is bent away from said lip part so as to define the
area at which non-contact with said annular supporting part begins.

- 10. (Currently Amended) The lip-type-scal <u>system</u> according to claim 9, wherein said lip part is 85 degrees to 98 degrees in material hardness according to JIS (Duro-A) hardness.
- 11. (Currently Amended) The lip-type-scal <u>system</u> according to claim 7, wherein said lip part is 85 degrees to 98 degrees in material hardness according to JIS (Duro-A) hardness.
 - 12.-14. (Canceled)